# WHAT HAVE WE LEARNED, Getting to good outcomes from Construction through Acceptance WSU Permeable Pavement Workshop Puyallup Sept. 2014



# ACI 522R-13 www.concrete.org

- National Pervious specification
- Revision to require
- 5 Technicians OR;
- 3+ Installers OR;
- 1 Craftsman

In specs; require copy of wallet cards or certificate upon submittal to validate current & valid crew certification



# TRAINING & CERTIFICATION

## **NRMCA PERVIOUS CONCRETE CERTIFICATION:**

- IS FOR CONTRACTORS, RM PRODUCERS, TESTING LABS
- PUBLIC AGENCY, LID, SPECIFIERS, ENGINEERS
- WELCOME TO AUDIT
- BENEFIT:

EVERYONE GETS THE SAME MESSAGES GOOD PERVIOUS / BAD PERVIOUS ESTABLISH EXPECTATIONS TO GET GOOD OUTCOMES IN THE FIELD



# NRMCA PERVIOUS CERTIFICATION

- ACI 522-13 Revisions
- TECHNICIAN
- Pass written exam with 75% or greater score
- No experience necessary
- Revise specs to Remove <del>Technician</del> ENTRY LEVEL



# NRMCA CERTIFICATION

- Installer: Pass written
- Requires completion of 10,000 sq. ft of pervious concrete work over 3 projects
- We require a performance
- evaluation at this level
- Revise specs to require 4 or more on crew



# NRMCA CRAFTSMAN- Highest Level

- Pass written test
- Requires completion of 10,000 sq. ft over 3 projects of pervious concrete work (Installer)
- Possess a ACI Concrete Finisher Technician or Craftsman at time of application
- Work experience required: Option A:
- Complete a performance evaluation and document pervious work over 1500 hours
- Option B: (no performance evaluation)
- Provide documentation of pervious concrete work exceeding 3,000 hours

# NRMCA CRAFTSMAN cont...

- Work experience is documented in square footage and hours using NRMCA work experience spreadsheet
- Documentation includes project detail info
- Craftsman application reviewed by Certification committee
- Craftsman interviewed by local Certification committee on project experience
- Full details at: www.nrmca.org
- Super Spec requires a Craftsman

BEST

# **SPECIFIERS ROLE**

- WORK WITH INDUSTRY RESOURCES BEFORE YOU START PLANNING
- BECOME KNOWLEDGABLE ON WHAT GOOD PERVIOUS IS; ESTABLISH EXPECTATIONS
- ON SITE: KNOW WHAT GOOD PERVIOUS LOOKS LIKE
- KNOW WHEN A MIX DESIGN LOOKS OFF
- KNOW WHEN CONTRACTOR IS NOT FOLLOWING PROCEDURES- NO short cuts



# SPECIFICATIONS: Keep it simple

- Do NOT Google "pervious specifications"
- Do NOT "Cut and Paste" or copy someone else's specifications!
- Pervious is a regional product, what works in Peoria may not work here!
- DO NOT over specify mix design; cement content, aggregates, non standard testing methods, voids, proprietary products...
- If you over specify...... you may own the outcome !!!
- Do NOT arbitrarily limit void content range IE: 15 +/- 3%
- Do NOT specify Strength, Slump, Air content
- DO use established ASTM tests for acceptance

# Specification- Key basics

- Require Installer level w/ documented certifications
- Cement- Do not specify specific content (Producer) Range 450 – 540 lbs. SCM - Yes
- Aggregates- ASTM C-33 Size and range- locally readily available aggregates- (controls cement content)
- Subgrade Prep / Forms / Mixing / some construction method direction (Jointing) ACI 522-10
- Curing: coverage / 7 days / opening / protection
- Final surface texture: smooth and uniform- Reference Slab
- Field Quality Control- require lab to be experienced

# **SPECIFICATIONS**

- Do reference ACI 522-13: "Specification for Pervious Concrete"
- Do reference ACI 522-10- Overview of construction practices
- Do use local Industry Resources: RM producers / WACA can assist / NRMCA Certified Contractors...
- ACI 330R-10: good for practical depth design or use PCA Design Pave software
- Do NOT specify "new" or proprietary products that promise a bazillion things but only increase or double material costs
- Do NOT use proprietary specs as supplied by others

-	

# **SPECIFICATIONS**

- Do require a PRECON of all parties supplying, placing, testing or accepting pervious-
- Do make sure spec has been read and understood
- Do use a REFERENCE SLAB: (not a mock up)
- Make sure reference slab is just not everyone's best effort- Use the slab as the standard for expectations and acceptance. Referee
- Do require certified crew members, require verification of certification at time of bid
- Do specify Installer level of above; Minimum of 4
- Do consider or specify minimum square footage / project portfolio expérience

# Mix design development

Less paste & lower

- = better aggregate coverage = better point to point
- content = better bonding
- = greater bond strength

### Too much cement = < incomplete

- hydration < aggregate bridging
- <poor bonding ,
  = RAVELLING</pre>



# Can you identify the difference?



# **Supplemental Materials**

- Increased use to improve workability, paste durability, freeze thaw resistance
- Fly Ash
- Slag
- Silica fume
- Balanced & Modern mixes



# What's new in testing?

No ASTM standards for Cylinders, Slump, Air Content Strength a function of the depth of the mass

ASTM C-09.49 Committee has or is developing:

✓ ASTM C-1688- Test Method for Density and Void Content of Freshly Mixed Pervious Concrete

✓ <u>ASTM C-1701</u> Test Method for Infiltration Rate of Pervious Concrete- not a acceptance test

✓ <u>NEW: ASTM C-1754</u>- Density and Void Content for hardened pervious concrete

In development or under consideration:
Abrasion Resistance, Fresh Concrete Density,
Compressive & Flexural Strength, Surface Durability
ACI 522- 2014 planning a Maintenance Committee





# New placing equipment ++

• Bunyan Springs

Committed **Pervious** Contractors are **Pushing standards** Higher



# Next: Color, Stamped, Decorative





# **Surface Uniformity**



# maintenance

- Efforts underway to establish a simple, effective methods to clean pervious
- Equipment is specialty & deep cleaning, washes & vacuums
- Anticipated to be available to public works or maintenance contractors

# Establish Expectations- The key to acceptance... is before & during placement





# Its not new anymore! Thank you!



