



low impact development technical workshop series

PIN Foundations

Topics

Applications

Design and Construction

Flow Control Credits



WASHINGTON STATE UNIVERSITY
EXTENSION

www.pinfoundations.com
©Copyright 2008, Pin Foundations, Inc.

Curtis Hinman
Senior Scientist
Herrera Environmental Consultants
chinman@herrerainc.com

The challenge is to better maintain native characteristics of soils during and after construction



In a typical, dense residential development there can be 50% more roof than road impervious area.

lid foundations

The typical construction approach is to strip, cut, fill and pound



Horizons
O 2 in
A 10 in
B 30 in
C 40 in


lid foundations

Management of large clearing and grading operations
expensive and time consuming.



lid foundations

Other Foundation Systems



Minimal footprint


Screw anchors

Vertical piling

Heavy Equipment
Site Pours
Carbon Release

lid foundations

The challenge is to better maintain native
characteristics of soils during and after construction



lid foundations

Wall Systems



Preparation

- Remove minimal material.
- Pea gravel then foam (isolates wall).
- Place forms, pour and drive pins.

Pin placement

- Preferred method is to place pins after pour.
- Can place pins before pour.

Can be applied to different construction applications.

lid foundations

Wall Systems




Can be used on slopes (stepped) but stormwater credit is reduced due to additional soil disturbance.

Conventional construction from the foundation up with some additional considerations.

lid foundations


Diamond Piers



Battered Pile Groups with Precast Concrete

- Reduced weight and volume
- No excavation, grading or site pours

Diamond Piers




- DP 50: 50 lbs. residential decks, 1 inch pins.
- DP 75: 75 lbs. homes and light commercial, 1.25 inch pins.
- DP 100: 100 lbs. homes and light commercial, 1.5 inch pins.
- DP 200: 200 lbs. homes and light commercial, 2.0 inch pins.

lid foundations

Diamond Piers

- Removable Pins
- Bracket Adjustment
- Height Adjustment



lid foundations

Diamond Pier Installation



- Two or three person crew.
- 20-30 minutes per pier.
- No excavation, heavy equipment or site repair.

lid foundations

Diamond Pier Installation



- ◆ Picking the right hammer: primarily driven by soil type determined during initial design.
- ◆ Installing pins...



lid foundations

Diamond Pier Installation



Removing pins... pin sits ~3/4 in above pier.



One and four bolt bracket configurations.



Height adjustment.

lid foundations


Diamond Pier Installation

Framing and utilities












Diamond Pier Design



- Phi angle: internal angle of friction...describes how granular soils hold up when stacked.
- Cohesive strength: characteristic of clay soils.
- In place unit weight.







4 pins of equal length per pier. Pin length includes that portion embedded in the pier.

lid foundations


Diamond Pier Design




Consider phi angle, cohesive strength and unit weight to determine equivalent bearing area.



Can cut pin if obstacle encountered, but 60% of length should remain.





Arching factor:
2x pile diameter.




lid foundations

Diamond Pier Submittals









PIN Inc. uses soil work to determine pier configuration. Architect determines loads and location of piers.

lid foundations

Structural Testing



- Concrete head restricts pin from changing angle and provides platform for structure...not load bearing.
- Structural limits
DP-100: 9000 Pounds



lid foundations

Structural Testing and Certification




Prescriptive load chart in normal construction conditions (soils, structure and site) for DP 50 and 75.



DP 100 and 200 requires soil testing and analysis (site specific) for load.

lid foundations

Performance and Durability



- Frost soil heave: pin angle retards uplift and point of pier cleaves/deflects soil around pier.
- Corrosion protection: low oxygen environment reduces corrosion.

lid foundations

Cost



- Pier costs = 2.5x model # (e.g. DP 100 = \$250).
- Cost driven by house size and load paths...i.e. number of piers.
- For poor soils DP cost increase ~ 10-15%. Conventional foundation can increase several hundred percent.
- If stormwater requirements not triggered SFR may not realize savings...that is changing.
- At subdivision scale reduced grading and excavating, and improved stormwater management can induce savings.

lid foundations

Flow Control Credits

No step forming

- Model as pasture on existing soil if roof runoff is dispersed on the up gradient side of structure according to BMP T5.10 (best flow control credit for low impact foundations).



lid foundations

Flow Control Credits

Step forming

- Use equation below to determine what portion of roof can be modeled as pasture on existing soil:

$$A_1 - [dC(0.5)/dP] \times A_1 = A_2$$



A_1 = roof area draining to up gradient
 dC = depth of cuts into soil profile
 dP = permeable depth of soil (A horizon + some B horizon)
 A_2 = roof area modeled as pasture on existing soil

lid foundations