

SpotBox4K - 32 ONVIF IP Camera Decoder +4K Display Box



OVERVIEW | FEATURES | DETAILED SPECIFICATION


Product Overview











The 'SpotBox4K' connects into the back of a monitor via HDMI offering a PC-LESS, LOW COST ONVIF IP camera viewing solution with a simple IR remote control

Program up to 32 IP ONVIF cameras, up to 16 of which can be viewed simultaneously on a 3840 x 2160 display resulting in excellent picture quality. All cameras are displayed in their native resolution including 3840x2160P30 8M Pixel (single view), 1080P30 (quad), 720P60 (9 view) and 480P30 (16 view).

'Spotbox4K' does not aim to compete with the NVR / VMS market - but simply provides an 'add on' solution to view existing IP cameras.



Key Features

-  Very Easy to Set Up & Use
-  Low Cost Solution
-  PC-LESS ONVIF IP Camera Viewing
-  Controlled with Simple IR Remote
-  Display up to 32 IP Cameras
-  4k 8MP decode H264/H265
-  View 1, 4, 9 or 16 IP Cameras
-  No VMS License Needed

SpotBox4K – 32 ONVIF IP Camera Decoder +4K Display Box



KEY BENEFITS | FEATURES | DETAILED SPECIFICATION

Detailed Specification

Cameras Supported : 1-32 Network Cameras. 16 cameras simultaneously , 32 in switching mode.

Camera Resolutions: 3840 x2160 P30 , 1080P30, 720P60 and 480P30 + intermediate resolutions

Display Format: 4x4 Grid max 480p each, 3x3 Grid max 720p60 each, 2x2 Grid 1080p30 or 1x1 Grid 4Kp30 (8MP)

Display Options: Static up to 16 or Timed Change up to 32 (dwell).

Stream Formats: 32x Programmable RTSP, MPEG-TS , HTTP or ONVIF profiles via web interface or API

Codec Type : H264 or H265

Maximum Display Capability: 3840 x 2160 / 4K / UHD (1080P displays also supported)

Remote Control : IR Remote Control supplied-

Remote Control Features: Select Single view (press 1-32) , 2x2 mode 3x3 mode and 4x4 mode. Power off, standby and full system reset. IR extender cable supplied for mounting behind a monitor.

On Screen Display: Name of Camera can be defined in web page and position on screen

Change Settings: Web Browser interface or SDK/API

Input Signal: Ethernet RJ45 Network connection

Firmware Upgrade:Network

Video Output : HDMI v1.4

Audio Output: Embedded via HDMI (single camera view only)

Dimensions 115 x 115 x 30mm

Weight: 235 grams

Power Consumption: 9.6 Watts Typically Supply Voltage 12 Volts DC

In the Box: SpotBox4K (ANT-37000), IR Remote, Multi Country 12v PSU, HDMI Cable, IR Extender, Quick Start User Guide.

Order Code: ANT-37000

