

## **Ad Specification:**

**All files should be in Adobe Portable Document Format (PDF)** version 1.3, preferred PDF files from QuarkXPress or InDesign using Pass4Press PDF settings. *Only high-res PDFs will be excepted.* 

- All transparency and layers flattened.
- Set Transparency Flattener to 2400 and 600; Images, 300 dpi for contones and a minimum 600 dpi (max. 1200) for lineart; Total Ink Limit in images is 300%.
- Fonts should be embedded/subset and should be PostScript Type1, TrueType or OpenType
- CMYK Colour only (No spot / Pantone colour or RGB colour)
- Ad image resolution 300dpi
- Ad TAC 300%, the use of ISOcoated\_v2\_300\_eci.icc is recommended.
- Neither custom transfer functions nor custom halftones should be used.
- Crop, Bleed and Trim marks must be used, unless it is for a quarter-page ad.
- Please allow .125in bleed for full-page and half-page ads.

## Full-Page Ad

■**Trim:** W 5in x H 8.5

[127mm x 215.9mm]

**Bleed:** W 5.25in x H 8.75 (.125in bleed)

[133.35mm x 222.25mm]

Live Area: W 4.5in x H 8in

[114.3mm x 203.2mm]

## Half-Page Ad

■**Trim:** W 5in x H 4.25

[127mm x 107.95mm]

■Bleed: W 5.25in x H 4.5 (.125in bleed)

[133.35mm x 111.125mm]

**Live Area:** W 4.5in x H 3.75in

[120.65mm x 101.6mm]



## **Quarter-Page-Fixed Ad** (no bleed)

■**Trim:** W 2.5in x H 2.125in

[63.5mm x 53.98mm]



