
NCHRP 20-68A
“US Domestic Scan Program”

Domestic Scan 15-02
Bridge Scour Risk Management

Rebecca Curtis
Bridge Management Engineer
Michigan DOT

Domestic Scan 15-02

“Bridge Scour Risk Management”

- This scan was conducted as a part of NCHRP Project 20-68A, the U.S. Domestic Scan program
- The program was requested by the American Association of State Highway and Transportation Officials (AASHTO), with funding provided through the National Cooperative Highway Research Program (NCHRP)

AASHTO / NCHRP U.S. Domestic Scan
Program



NCHRP 20-68A

U. S. Domestic Scan Program

- The Program is a multi year project conducting 3-4 scans per year.
- Each scan is selected by AASHTO and the NCHRP 20-68A Project Panel.
- Each scan addresses a single technical topic of broad interest to many state departments of transportation and other agencies.
- The purpose of each scan and of Project 20-68A as a whole is to accelerate beneficial innovation by:
 - ❑ facilitating information sharing and technology exchange among the states and other transportation agencies;
 - ❑ identifying actionable items of common interest .

Scan Team

Rebecca Curtis –AASHTO Chair

Bridge Management Engineer
Michigan DOT

Xiaohua “Hanna” Cheng, PhD, P.E.

Civil Engineer, Bureau of Structural Engineering
New Jersey Department of Transportation

Stephanie Cavalier, P.E.

Bridge Scour Manager
Louisiana Department of Transportation and
Development (LADOTD)

Rick Marz

The head of Wisconsin Inspection Program
Bureau of Structures Maintenance Chief
Wisconsin DOT

Jon Bischoff

Geotechnical Engineer Specialist
Utah Department of Transportation

Kevin Flora

Senior Bridge Engineer, Structure Maintenance and
Investigations
California Department of Transportation
(CALTRANS)


Hani Nassif, P.E., Ph.D., Professor - SME

Department of Civil & Env. Engineering
Rutgers, The State Univ. of New Jersey

AASHTO / NCHRP
U.S. Domestic Scan Program



Scan 15-02 Team Members Home State and Invited Agency States



NCHRP Panel's General Guidance to the Scan Team

“This scan will examine practices of states, counties, metropolitan areas, municipalities and other transportation agencies, to identify and document successful approaches to reducing bridge flooding and scour risk through appropriate use of countermeasures. The scan will also consider how innovative bridge owners assess structural vulnerability or bridge scour susceptibility.”



NCHRP Panel's General Guidance to the Scan Team (cont.)

“The scan team would examine innovative approaches such as

- **Risk-based** decision analysis for
 - selection and installation of countermeasures
 - selection, installation, and management of monitoring systems
 - bridge replacement rather than use of countermeasures or monitoring systems
- **Inspection** procedures for scour countermeasures
- **Alert systems** to trigger inspections during flood events
- **Road-closing** and -reopening decision process
- Bridge inspection and documentation procedures during and after a flood event, including updating bridge inspection reports and the agencies' **Scour Plan of Action.**”



NCHRP Panel's General Guidance to the Scan Team (cont.)

*“The scan team will focus on practices for **inspection, monitoring, countermeasure selection and placement, and risk management** for scour-critical and scour-susceptible bridges individually and in networks of varying sizes.”*



NCHRP Panel's Anticipated Outcomes

*“By documenting and sharing successful practices the scan team will produce a valuable resource for use by bridge owners, state and local bridge inspectors, bridge designers and bridge management staff in **reducing the risk** to the travelling public due to flooding and scour.”*




Team's Approach

- Perform Desk Scan and Literature review
- Identify Topics that are related to Scour Risk Management
- Produce Amplifying Questions/Survey for Participating States based on Identified Topics
- Compile Responses to Amplifying Questions
- Hold Workshop of Invited States
- Establish Findings and Recommendations



Responses to Selected Amplifying Questions


■ General Information about Agency (Continued)



Responses to Selected Amplifying Questions


■ Topic 1: General Procedures and Risk Analysis

Does your agency follow FHWA's guidelines for scour design for new bridges?




■ Yes ■ No

Does your agency follow FHWA's guidelines for scour countermeasures?




■ Yes ■ No

Are you considering or adopting new changes in your scour assessment and mitigation process?




■ Yes ■ No

Do you consider using a vulnerability index?



■ Yes ■ No

Are you considering adding Scour as a risk factor in your transportation asset management plan?




■ Yes ■ No

Responses to Selected Amplifying Questions


■ Topic 2: Scour Modeling and Analysis

Does your agency use HEC-18 equations?




■ Yes ■ No

Do you perform a detailed/refined Hydraulic analysis?




■ Yes ■ No

Do you perform a cost-benefit analysis prior to performing structural modeling?



■ Yes ■ No

Do you have a case study that would demonstrate the success of the detailed hydraulic and/or structural modeling and analysis?



■ Yes ■ No

Do you use computer software for scour assessment and/or risk mitigation (e.g., SRH-2D, HEC-RAS, FB-Multiplier, etc.)?




■ Yes ■ No

Responses to Selected Amplifying Questions


■ Topic 3: Monitoring and Field Inspection of Scour Critical Bridges

Has your state used sonar on a line rod in order to measure scour depths at some bridges on a daily basis?




■ Yes ■ No ■ Unknown

Do you have state-specific criteria to reduce the frequency of field inspections for scour critical bridges?



■ Yes ■ No

Are you using a Network-wide web-based monitoring system for monitoring rainfall, flooding etc. and pro-active notification of personnel during flood events?




■ Yes ■ No



Responses to Selected Amplifying Questions


■ Topic 4: Design Installation and Sustainability of Countermeasures

Do you have state-specific guidelines for designing and installing countermeasures for scour?




■ Yes ■ No

Do you have guidelines for selecting appropriate countermeasures?




■ Yes ■ No

Does a criterion exist that prevents changing the 113 code after countermeasures are added?




■ Yes ■ No

Are there any countermeasures or foundation types that your department will not use?



■ Yes ■ No

Do you have agency-defined elements for your element level inspection for scour countermeasures?




■ Yes ■ No

Responses to Selected Amplifying Questions


■ Topic 5: Plan of Action

Do you have a statewide emergency response for inspection and monitoring of a large network of bridges under an extreme event?




■ Yes ■ No

If structural or channel improvements or installations of countermeasures have been made, do you request a re-evaluation?



■ Yes ■ No

Do you have emergency action protocols?



■ Yes ■ No

Team's Approach(Continued)

- the Scan Team identified topics that are essential for the understanding of Scour Risk Management as follows:
 - General Procedures and Risk Analysis
 - Scour Modeling and Analysis
 - Monitoring and Field Inspection of Scour Critical Bridges
 - Design, Construction, and Sustainability of Countermeasures
 - Plan of Action (POA)



Topic 1: General Procedures and Risk Analysis

Findings:


- ❑ Most states used criticality and others used Probabilistic Approaches to help perform Risk Analysis.
- ❑ A number of States perform Vulnerability analysis and table scoring to help mitigate scour
- ❑ Many states have strong Teams of Structural, Hydraulic, and Geotechnical Engineers
- ❑ Definition of risk and minimizing Uncertainty using various methods

Criteria	Rehabilitation	Replacement
Construction Cost	Lower Initial Cost = \$18,790,000	Higher Initial Cost = \$ 43,392,000
Life Cycle Costs	Net Present Value = \$ 27,266,671 Equiv. Uniform Annual Cost = \$ 1,123,598	Net Present Value = \$ 47,616,837 Equiv. Uniform Annual Cost = \$ 1,962,183
Functionality	Remains the same	Wider roadway deck promotes safety & accommodates center channelization lane for left turns
Long Term Reliability	Substructures would be 130 years old before bridge is replaced Additional future scour countermeasures likely required	New bridge built to current codes and requirements Scour resistant Substructure
Risk	Greater potential for unforeseen issues with major structural repairs Higher likelihood for possible issues with 80-year old substructures	Fewer unknowns with all-new construction Ability to fully consider potential issues in new design
Constructability	Specialized & complex repairs for track and tread replacements Jacking and shoring leaves Major work during winter	Typical Movable Bridge Construction
Construction Disruption	9-Month Roadway Closure	21-Month Roadway Closure



State Practices: Louisiana DOTD

- Pile Testing-Dispersive Wave & Parallel Seismic



State Practices: Texas DOT

- Unknown Foundation Determination for Scour
 - Inference Method
 - Geophysical Method

INFERENCE METHOD




Figure 7-11. Ensemble Prediction for MLP-PL10 for Concrete Piling.




Figure 7-12. Ensemble Prediction for MLP-PL11 for Drilled Shafts.

State Practices: Texas DOT (Cont'd)

- Inference Method



Worked for bridges with concrete piling and drilled shafts, but did not work well for timber piling.




State Practices: Texas DOT (Cont'd)

■ Geophysical Method



Figure 11-6. Bridge 14 ERI Fieldwork.

Resistivity
Profiling




State Practices: Texas DOT (Cont'd)

- Geophysical Method




Polarization Imaging



State Practices: Florida DOT


Unknown Foundations Process



* See Procedural Manual: Reclassify Unknown Foundation Bridges for a description of these steps and procedures.

State Practices: New York State DOT

- Vulnerability Rating Procedure



State Practices: Colorado DOT

- Scour Critical Bridge Program

*Data
Collection*

Scour Analysis

Recommendations

Final Report




SEIR
Accelerometer Data

Date: 4/12/2009
Sampling Rate: 20 us Record Size: 2048
Number of Record: 6
Trigger Level: 0.5
Trigger Delay: 2000 us Trigger Ch: 8
Channel Setup Total: 3
Channel: 6 7 8
Delta F: 24.4141 Hz Period: 40960 us
Nyquist: 25000 Hz V: 125000 ft/sec


Results (OP File = None)
Plot 1: Gain = 200 scale 0%
Plot 2: Depth = 0. ft T = 0. 0
Plot 3: Depth = 49.4 ft T = 14600 3

Start Acq (View) Start Acq (Run) Cancel
Reload Data Open Recall



Topic 1: General Procedures and Risk Analysis

- Conclusions:
 - ❑ Scour Risk Management is a complex process and requires input and open communication from multiple disciplines.
 - ❑ Due to limited resources, states need to prioritize risk assessment including advanced design, monitoring, and design of countermeasures.
 - ❑ Prioritization appears to be based on criticality alone with limited consideration to vulnerability



Topic 1: General Procedures and Risk Analysis

- Recommendations:
 - States need to form scour committees with interdisciplinary capabilities (i.e., Engineers from Geotechnical, Structural, and Hydraulics areas)
 - scour is a nation-wide threat -AASHTO should create a multidisciplinary task force that would develop guidelines and specifications for scour mitigation design and to serve as a clearing house for new innovations.
 - Due to limited resources, States should consider using Risk Analysis to prioritize how to best apply their limited resources rather than using vulnerability analysis to identify scour critical bridges.




Figure 1 – Six Steps for Conducting a Vulnerability Assessment



Topic 2: Scour Modeling and Analysis


Findings:

- ❑ Better testing methods of soil and rock is needed. (i.e. Erosion test for site-specific type of soils, Rock Erosion/Texas Cohesive soil methods /Predictive Models)
- ❑ Use of 2D/3D hydraulic modeling to simulate stream flow
- ❑ Texas velocity chart for verifying modeling. Texas Data management for quality control/assurance. Data checks, such as in Texas case, can help provide quality control for scour predictions.
- ❑ Agencies are using Google earth to study historic stream migration patterns
- ❑ HEC-18 provides a scour methodology for cohesive soils but requires getting shear stress by testing.



State Practices: Florida DOT

Local Scour Equations



CLEAR-WATER SCOUR

$$0.47 \leq \frac{V}{V_c} \leq 1$$

$$\frac{y_s}{D^*} = 2.5 f_1 \left(\frac{y_0}{D^*} \right) f_2 \left(\frac{V}{V_c} \right) f_3 \left(\frac{D^*}{D_{50}} \right)$$

where $f_1 \left(\frac{y_0}{D^*} \right) = \tanh \left[\left(\frac{y_0}{D^*} \right)^{0.4} \right]$

$$0.47 \leq \frac{V}{V_c} \leq 1$$

$$f_2 \left(\frac{V}{V_c} \right) = 1 - 1.75 \left[\ln \left(\frac{V}{V_c} \right) \right]^2$$

$$f_3 \left(\frac{D^*}{D_{50}} \right) = \frac{D^*/D_{50}}{0.4(D^*/D_{50})^{1.2} + 10.6(D^*/D_{50})^{-0.13}}$$


LIVE-BED SCOUR

$$1 \leq \frac{V}{V_c} \leq \frac{V_{lp}}{V_c}$$

$$\frac{y_s}{D^*} = f_1 \left(\frac{y_0}{D^*} \right) \left[2.2 \left(\frac{V - V_c}{V_{lp} - V_c} \right) + 2.5 f_3 \left(\frac{D^*}{D_{50}} \right) \left(\frac{V_{lp} - V}{V_{lp} - V_c} \right) \right]$$


State Practices: Florida DOT

- Rock Erosion Measurements with the Rotating Erosion Test Apparatus (RETA)



State Practices: Missouri DOT

- Streambank Stability/Lateral Migration



LiDAR Scan





State Practices: Caltrans

- Improved Scour Measurements



State Practices: Caltrans (Cont'd)


- Detailed Hydraulic Modeling



Topic 2: Scour Modeling and Analysis

Conclusions:


- Advanced methods for modeling and material testing can be used to enhance scour predictions.
- Using external data sources can enhance the quality control of scour predictions.



Topic 2: Scour Modeling and Analysis

Recommendations:

- ❑ Materials testing for cohesive soils or rocks can be performed using new techniques such as those developed by Florida DOT or FHWA
- ❑ States are recommended to use 2D/3D models that are shown to be very useful in advanced cases. There is a need to identify the conditions or parameters when the 2D models can be applied.
- ❑ Encourage States and other agencies, involved with 2D modeling, to participate in NHI courses and other training workshops.



Topic 3: Monitoring and Field Inspection of Scour Critical Bridges

Findings:

- Improved methods to predict scour depth (i.e., 2D modeling to include better parameters for the HEC18 equations).
- Improved and safer inspection methods (i.e. Sonar versus diving). Use of 3-D Sonar in lieu of Under Water Inspection (UWI).
- A number of states have had successful relationship with USGS through contracts and partnership.
- Smart Phone Point Cloud

SCOUR MONITORING (ea.)

Michigan Bridge Element Inspection Manual


Description: This element defines scour monitoring systems applied to substructure elements.

No.	Name	CS Table	Description
838	Scour Monitoring	12	Scour monitoring systems.

Quantity Calculation: The quantity for this element is measured per bridge and includes all devices attached to the bridge for monitoring velocity or scour depths.



Scour Monitoring Device



Revised 03/05/2015

Page 43



State Practices: Tennessee DOT

■ Bridgwatch™ Program

Internet based application

Implemented 2004

US Engineering Solutions
Public Safety Through Real-Time Structure Monitoring

Company Solutions News & Information Client Access

About Us Clients Contact Us Partners
BridgeWatch DamWatch FloodWatch Overview
Industry News Links & Resources Media Room USES News

Client Access
Click your logo to access your login page.

Iowa Department of Transportation
TDOT

BridgeWatch v6.0 from USEngineeringSolutions - Mozilla Firefox

http://bridgwatch.us/tdot/main/main.html

BridgeWatch | Tennessee Department of Transportation

admin | logout | about | help

Watch List

100 YR NEXRAD 08-19-10 830394
50 YR NEXRAD 08-19-10 830394
500 YR NEXRAD 08-18-10 67SRC
200 YR NEXRAD 08-18-10 67SRC

Display List Refresh List

Geography

Data Sources

Bridge	Year Peak	Type	Exceedance	County	Region
05038030001	100	NEXRAD	3.69	Blount County	Re...
05038030001	25	NEXRAD	3.99	Blount County	Re...
050A5320001	25	NEXRAD	2.27	Blount County	Re...

Customizable with TRIMS data


Monitors 24 / 7 / 365

Default thresholds




State Practices: Idaho DOT

■ Idaho Stream Gauging Locations





Explanation - Percentile classes							
●	●	●	●	●	●	●	○
Low	<10	10-24	25-75	76-90	>90	High	Not-ranked
	Much below normal	Below normal	Normal	Above normal	Much above normal		






State Practices: Idaho DOT

■ SNOTEL Sites in Idaho



State Practices: Iowa DOT


■ Remote Hydrographic Surveying System



ECHOSOUNDER & GPS + RADIO CONTROL + DATA TELEMETRY → REAL TIME MAPS

State Practices: Mississippi DOT

■ Bridge Scour Monitoring




Bridge Scour Monitoring




State Practices: Mississippi DOT (Cont'd)

- Real time scour monitoring gage (15 min interval)

02480273 Pascagoula River at Interstate 10 at Crooked Bayou



PASCAGOULA RIVER AT INTERSTATE HIGHWAY 10
PIER 184 R
SEPTEMBER 20, 2005




Bridge Scour Monitoring




State Practices: Michigan DOT

- 3D BRIDGE app



State Practices: Idaho DOT

■ Scour Monitoring Research



State Practices: Caltrans

■ Flood Monitoring System for State Bridges

ArcGIS REAL-TIME MONITORING OF BRIDGE PIER SCOURING DURING FLOOD EVENTS

New Map Create Presentation Saravana


Details Add Basemap

Save Share Print Measure Bookmarks Find address or place

About Content Legend

Contents

- Dist12 Bridges
- Dist11 Bridges
- Dist10 Bridges
- Dist09 Bridges
- Dist08 Bridges
- Dist07 Bridges
- Dist06 Bridges
- Dist05 Bridges
- Dist04 Bridges
- Dist03 Bridges
- Dist02 Bridges
- Dist01 Bridges
- Bridges with Issues
- Caltrans District Map
- All Live Stream Gauges
- Additional Stream Gauges
- 3-Day Forecast of Total Precipitation (Inches)
- Realtime Rainfall (LB-GR:0.01-0.1, DG-YL:0.1-0.5, OR: 0.5 inch/hr)



Esri.com ArcGIS Marketplace Help Terms of Use Privacy Contact Esri Report Abuse

Earthstar Geographics | Esri, HERE | Esri | VDEM GIS, USGS | ©2013 Esri | Esri, HERE, DeLorme

POWERED BY esri



MDOT
Michigan Department of Transportation
BRIDGE DEVELOPMENT


State Practices: Caltrans (Cont'd)

- Monitoring



State Practices: Caltrans (Cont'd)

- SMART Rocks



- Acoustic Stage Gage



State Practices: Caltrans (Cont'd)

■ Tilt Sensor Instrumentation



INFRASTRUCTURE TECHNOLOGY INSTITUTE
Feather River Bridge #18-0009
 STRUCTURAL HEALTH MONITORING



ABOUT THE PROJECT

[Feather River Home](#)
[Feather River Documents](#)
[Scour Monitoring Home](#)


LONG-TERM DATA

[Past 24 Hours](#)
[Past 72 Hours](#)
[Past Week](#)
[Past Month](#)
[Past 90 Days](#)
[Entire Project](#)
[Custom Date Range](#)

CONTACT US

NU-ITI
 2133 Sheridan Rd
 First Floor
 Evanston, IL 60208
 Tel: 847-467-6684
dkosnik@northwestern.edu

Hourly Data past 72 hours - latest data taken Sat, Apr 30, 2011 17:00 PST



Topic 3: Monitoring and Field Inspection of Scour Critical Bridges

Conclusions:

- Advanced technology such as sonar can be applied effectively to enhance data collection efficiency and inspector safety.
- External data sources, such as USGS generated data, are essential for the successful implementation and management of scour programs in the USA

Michigan Bridge Element Inspection Manual

CS TABLE 10 – SCOUR PROTECTION

Defects	Condition State 1	Condition State 2	Condition State 3	Condition State 4
	GOOD	FAIR	POOR	SEVERE
Scour or Erosion	None.	Countermeasure is substantially effective. Scour or Erosion exists without undermining.	Countermeasure device has limited effectiveness Erosion may be evident with undermining of countermeasure.	The channel protection device or scour countermeasure are unstable, missing or no longer effective.
Material Defect (scaling, abrasion, spalling, corrosion, cracking, splitting and decay)	Insignificant or minor defects.	Countermeasure device is substantially effective. Extensive minor to isolated advanced defects.	Scour countermeasures have limited effectiveness. Extensive advanced to major defects.	
Damage (unraveling, displacement, separation, and sagging)	Insignificant or minor damage.	Countermeasure device is substantially effective. Extensive minor to isolated advanced damage.	Scour countermeasures have limited effectiveness. Extensive advanced to major damage.	

Topic 3: Monitoring and Field Inspection of Scour Critical Bridges



Recommendations:

- States should establish collaborative partnerships with USGS and other agencies to facilitate sustainable data collection for scour predictions.
- AASHTO and FHWA should establish partnerships with USGS and other agencies for innovative applications to advance the State-of-Art of flooding on highway infrastructure.
- States should work proactively with FHWA for use and acceptance of advanced technologies for under water inspection (e.g., sonar) to improve data collection and divers' safety.
- Continued and future research is needed to enhance the capabilities of various systems to measure real-time scour. Moreover, communication and dissemination of various research projects is needed to raise awareness of accomplishments.



Topic 4: Design, Construction, and Sustainability of Countermeasures

Findings - A number of States have had good experience with various countermeasure designs.



State Practices: Minnesota DOT

- Countermeasure Techniques



(Matrix Riprap,
partially grouted
riprap)



Geobags



State Practices: Missouri DOT

- Smart Rocks Scour Monitoring/Riprap Effectiveness

- Original Concepts
- 3 Monitoring Strategies






Figure 1.5 Scour Countermeasure Monitoring



(a) Geometry of Magnets and Encasement



(b) Prototype in Spherical Shape

Figure 4.43 Design and Prototype of Magnets and Passive Smart Rocks



Topic 4: Design, Construction, and Sustainability of Countermeasures

Conclusions:

- States had varying levels of success in implementing the same countermeasures.
- The design and installation of countermeasures needs to be appropriate given all parameters
- States had success in Innovative techniques in applying countermeasures such as Articulated Mattresses, GeoBags, Caged Blocks, AJAX, rock riffle.
- Countermeasures have a shorter lifespan compared to the design and service life of the bridge.



Topic 4: Design, Construction, and Sustainability of Countermeasures

Recommendations:

- States are encouraged to share lessons learned based on their specific experience with countermeasure design and application (e.g., Ski, etc .)
- States should pay more attention to inspecting countermeasures during construction and routine inspections.
- Establishment of a body to help disseminate the information related to the performance of various types of countermeasures is needed.



Topic 5: Plan of Action (POA)

Findings:

- Implementing inspection during significant flood events can be a strain on departmental resources.

SCOUR EVALUATION					
Item 113	Scour Criticality	3 SC - Unstable	Source of Item 113	Assessed	
Item 71	Waterway Adequacy	7 Above Minimum			
Level I Assessment		Yes			
Level II Analysis		Yes			
Document Date	Document Name			Document Type	
03/07/2016	MDOT Level Two Example.pdf			Level II	
03/07/2016	MDOT Level One Example.pdf			Level I	
Calculated Values					
Scour Analysis Frequency	25 Year	50 Year	100 Year	500 Year	Comments
Anticipated Surface Elevation (ft)	581.75	585.63	600.21	602.3	
Distance Below Bottom Chord (ft)	5.0	4.5	0.0	0.0	Pressure Flow at the 100 Year
Anticipated Flow (cubic ft/sec)	150.0	180.0	200.5	225.24	
Anticipated Pressure Flow (Y/N)	N	N	Y	Y	

Topic 5: Plan of Action (POA)

Conclusions:

- Only few states included information useful to the stakeholders of the POA rather than purely meeting the FHWA mandate.
- Some States are using innovative methods (e.g., BridgeWatch or ArcGIS Online) to implement POA's
- It has been observed that during extremely large flood events, bridges that are not scour critical were also impacted.



Topic 5: Plan of Action (POA)

Recommendations:

- It is recommended that States consider additional information (e.g., cross section, whether the bridges on the detour route are scour critical, etc.) to enhance their POA which could be useful to the stakeholders.
- States are recommended to develop emergency protocols for widespread flood events. (POA are bridge-specific)
- States should create risk-based prioritization for implementing POA during flood events, which could be based on specific trigger for specific bridges. .



Next Steps

- Scan Team will develop a Scan Report:
 - Document “Findings” and “Conclusions”.
 - Include a Dissemination Plan.
 - Provide recommended next steps.
 - Invited states will review and approve their state’s info prior to finalizing and publishing.

Final Report and other material
will be made available on the
web at

www.domesticscan.org

2017

