

## **Ad Specification:**

All files should be in Adobe Portable Document Format (PDF) version 1.3, preferred PDF files from QuarkXPress or InDesign using Pass4Press PDF settings. Only high-res PDFs will be excepted.

- All transparency and layers flattened. •
- Set Transparency Flattener to 2400 and 600; Images, 300 dpi for contones and a minimum • 600 dpi (max. 1200) for lineart; Total Ink Limit in images is 300%.
- Fonts should be embedded/subset and should be PostScript Type1, TrueType or OpenType •
- CMYK Colour only (No spot / Pantone colour or RGB colour)
- Ad image resolution 300dpi
- Ad TAC 300%, the use of ISOcoated\_v2\_300\_eci.icc is recommended.
- Neither custom transfer functions nor custom halftones should be used.
- Crop, Bleed and Trim marks must be used, unless it is for a guarter-page ad.
- Please allow 3mm bleed (.125in) for full-page and half-page ads.

## Full-Page Ad

Trim:	W 210mm x H 297mm [8.28in x 11.69in]	
Bleed:	W 216mm x H 303mm (3mm all round) [8.50394in x 11.93in] (.125in bleed)	A4
Live Area:	W 190mm x H 277mm [7.5in x 10.90in]	

## Half-Page Ad

■Trim:	W 210mm x H 144mm	
	[8.28in x 5.67in]	
Bleed:	W 216mm x H 150mm (3mm all round)	
	[8.50394in x 5.90in] (.125in bleed)	
Live Area:	W 190mm x H 134.2mm	
	[7.5in x 5.28in]	

## Quarter-Page-Fixed Ad (no bleed)

Trim: W 93mm x H 135mm [3.66in x 5.31in]



